

LOBACARE® V6 Finish gloss & satin



V6 Finish gloss & satin are waterborne care products for use on finished wood, cork, PVC and Linoleum floorings. When applied V6 Finish provides a fresh protective layer bringing a shine to worn floors without recoating or sanding.

Recommended Use:

For refreshing finished wood, cork, PVC and Linoleum without the expense of a full recoating or sanding.

- Provides a protective layer
- VOC compliant
- Excellent adhesion
- Easy to apply

Technical Data

Article No.	10189	Coverage	250 square feet per 1 quart bottle
Package Size	1 quart	Application Tool	Terry cloth or microfiber mop, T-bar applicator
Packaging	Case: 12 x 1 US quart plastic bottle Pallet: 660 x 1 US quart	Drying Time	Slightly stressable After 1 hours Fully stressable After 12 hours
US Regulatory VOC	303 grams per liter V6 Finish gloss 99 grams per liter V6 Finish satin		
Storage	41°F to 77°F. KEEP FROM FREEZING.		
Shelf life	24 months in unopened original containers.		

Directions

- BEFORE USING, READ AND UNDERSTAND ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-Wakol Technical Service at 1-800.230.6456.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks and puddles and lap marks.
- Floor must be free from wax, oils and dirt

Maintenance Process:

- 1.) Clean floor using Hardwood Floor Cleaner making sure the floor is free from, oils, waxes and dirt.
- 2.) Apply a thin coat of V6 Finish gloss or satin and allow to dry.
- 3.) Allow 3 days curing before using any cleaners or maintenance products on freshly applied V6 Finish gloss or satin.

Deep Cleaning:

V6 Finish cannot be completely removed by deep cleaning cork and wood floors. In order to check suitability and adhesion always do a test area first. If the adhesion is not sufficient a deep cleaning might improve the adhesion.

Compatibility:

When this product is used in combination with other LOBA products also the Technical Information of these products has to be followed. Always prepare test areas to determine suitability of other products than LOBA. V6 Finish can only be recoated with itself. Refinishing with other Finishes is not possible due to insufficient adhesion.

LOBACARE[®] V6 Finish gloss & satin

Clean-up:

Use water to clean tools immediately after use. Do not dispose left overs with household garbage; unused product must not be poured into the sewage system, but must be brought to the chemical waste disposal according to local, state, and federal regulations after complete curing.

Maintenance:

Floor Care:

Clean floor with wet cloth or mop only after full cure is reached. Do not clean with water or detergent during the first week. After one week we recommend the use of Hardwood Floor Cleaner.

Put walk-off mats at all entrance doorways to minimize dirt and grit. Sweep or vacuum daily and damp-wipe with Hardwood Floor Cleaner. Use felt pads under furniture legs and appliances. Place furniture and other heavy appliances carefully.

Plasticizer containing materials:

Plasticizer containing materials e.g. carpet padding, furniture padding, chair rolls, elastic glues etc. could lead to softening and discoloration of the finish.

Visit www.loba-wakol.com for additional information and instruction about floor care and maintenance.

Safety Precautions:

Even when working with low-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Make sure working areas are ventilated sufficiently. Clean left-overs off of hands. Change soiled clothes. Ventilate working rooms during working and drying time avoiding draft.

First Aid:

If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If breathing is difficult or other respiratory complaints, get medical attention. In case of contact, immediately flush eyes or skin with plenty of water. Do not use solvents or thinners. Remove contaminated clothing or shoes. For eye contact, rinse opened eye for several minutes under running water. Call a physician if irritation occurs.

WARNING! If you scrape, sand or remove old paint from wooden floors, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Special Information:

The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the Technical Information concerning those products.