Safety Data Sheet ULTRACOAT EASY 10

Safety Data Sheet dated: 07/02/2023 - version 4



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ULTRACOAT EASY 10

Trade code: 9073756

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy paint

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel. +(39)02376731 (office hours) - Fax: +39-02-37673.214 - www.mapei.it

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

Centro antiveleni, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via Antonio Cardarelli 9, Napoli - Tel. 081 5453333

Centro antiveleni, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo Brambilla 3, Firenze - Tel. 055 7947819 Centro antiveleni, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia - Tel. 0382 24444

Centro antiveleni, Azienda ospedaliera Niguarda Ca' Granda, piazza Ospedale Maggiore 3, Milano - Tel. 02 66101029

Centro antiveleni, Azienda ospedaliera "Papa Giovanni XXIII", Tossicologia clinica, Dipartimento di farmacia clinica e farmacologia, piazza OMS 1, Bergamo - Tel. 800 883300

Centro antiveleni Policlinico "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155, Roma - Tel. 06 49978000

Centro antiveleni del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino Gemelli 8, Roma - Tel. 06 3054343

Centro antiveleni, Azienda ospedaliera universitaria Riuniti, viale Luigi Pinto 1, Foggia - Tel. 800 183459

Centro antiveleni, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA, piazza Sant'Onofrio 4, Roma - Tel. 06 68593726

Centro antiveleni dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo Trento, piazzale Aristide Stefani, 1 - 37126 Verona - Tel. 800 011858

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH208 Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >=0.1%

Other Hazards: No other hazards

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 1 of 11

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: ULTRACOAT EASY 10

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥5 - <10 %	dipropyleneglycol methyl ether	CAS:34590-94-8 EC:252-104-2	Substance with a Union workplace exposure limit.	01-2119450011-60-xxxx
≥0.1 - <0.25 %	2,4,7,9-tetramethyldec-5-yne-4,7-diol	CAS:126-86-3 EC:204-809-1	Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412	01-2119954390-39-xxxx
≥0.016 - <0.025 %	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	- CAS:2634-33-5 EC:220-120-9 Index:613-088- 00-6	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411	
			Specific Concentration Limits: C ≥ 0,05%: Skin Sens. 1 H317	
<0.0015 %	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	EC:611-341-5 Index:613-167-	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic:100, M-Acute:100	
			Specific Concentration Limits: C ≥ 0,6%: Skin Corr. 1C H314 0,06% ≤ C < 0,6%: Skin Irrit. 2 H315 C ≥ 0,6%: Eye Dam. 1 H318 0,06% ≤ C < 0,6%: Eye Irrit. 2 H319	
			C ≥ 0,0015%: Skin Sens. 1A H317	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Not available

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

Not available

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 2 of 11

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

6.1. Control parameters							
Community Occupational Exposure Limits (OEL)							
	OEL Type	Country	Occupational Exposure Limit				
dipropyleneglycol methyl ether CAS: 34590-94-8	SUVA		Long Term: 300 mg/m3 - 50 ppm; Short Term: 300 mg/m3 - 50 ppm				
	NDS		Long Term: 240 mg/m3				
	National		Long Term: 303 mg/m3 - 50 ppm; Short Term: 600 mg/m3 - 100 ppm				
	Nationa	I	Long Term: 300 mg/m3 - 50 ppm; Short Term: 450 mg/m3 - 75 ppm Short-term value, 15 minutes average value				
	Nationa	il	Long Term: 310 mg/m3 - 50 ppm hud				
	Nationa	ıl	Long Term: 300 mg/m3 - 50 ppm H				
	NDSCh		Long Term: 480 mg/m3				
	EU		Long Term: 308 mg/m3 - 50 ppm Skin				
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm Skin - Eye and URT irr, CNS impair				
	DFG	GERMANY	Ceiling - Short Term: 310 mg/m3 - 50 ppm				
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm Skin - potential significant contribution to overall exposure by the cutaneous route;CNS impairment;eye and upper respiratory tract irritation				
	Nationa	I SWEDEN	Long Term: 300 mg/m3 - 50 ppm				

Print date 10/02/2023 Production Name **ULTRACOAT EASY 10** Page n. 3 of 11 National FRANCE Long Term: 308 mg/m3 - 50 ppm National SPAIN Long Term: 308 mg/m3 - 50 ppm

National GREECE Long Term: 600 mg/m3 - 100 ppm; Short Term: 900 mg/m3 - 150 ppm

National DENMARK Long Term: 309 mg/m3 - 50 ppm National FINLAND Long Term: 310 mg/m3 - 50 ppm National GERMANY Long Term: 310 mg/m3 - 50 ppm

National PORTUGAL Long Term: 308 mg/m3 - 50 ppm; Short Term: 150 ppm

National NORWAY Long Term: 300 mg/m3 - 50 ppm; Short Term: 375 mg/m3 - 75 ppm

National BELGIUM Long Term: 308 mg/m3 - 50 ppm

NDS POLAND Long Term: 240 mg/m3 NDSCh POLAND Short Term: 480 mg/m3

CHE SWITZERLAN Short Term: 300 mg/m3 - 50 ppm

D

NDS NETHERLAND Long Term: 300 mg/m3

S

National CZECH Long Term: 270 mg/m3

REPUBLIC

National HUNGARY Long Term: 308 mg/m3

Malaysi MALAYSIA Long Term: 606 mg/m3 - 100 ppm

a OEL Skin notation

National ESTONIA Long Term: 308 mg/m3 - 50 ppm
National LATVIA Long Term: 308 mg/m3 - 50 ppm
National CZECH Ceiling - Short Term: 550 mg/m3

REPUBLIC

National SLOVAKIA Long Term: 308 mg/m3 - 50 ppm National SLOVENIA Long Term: 308 mg/m3 - 50 ppm

National UNITED Long Term: 308 mg/m3 - 50 ppm; Short Term: 924 mg/m3 - 150 ppm

KINGDOM

National BULGARIA Long Term: 308 mg/m3 - 50 ppm
National ROMANIA Long Term: 308 mg/m3 - 50 ppm
TUR TURKEY Long Term: 308 mg/m3 - 50 ppm

National LITHUANIA Long Term: 308 mg/m3 - 50 ppm; Short Term: 450 mg/m3 - 75 ppm

National CROATIA Long Term: 308 mg/m3 - 50 ppm EU Long Term: 308 mg/m3 - 50 ppm

Behaviour Indicative

Possibility of significant uptake through the skin

National SLOVENIA Long Term: 308 mg/m3 - 50 ppm; Short Term: 308 mg/m3 - 50 ppm National LITHUANIA Long Term: 300 mg/m3 - 50 ppm; Short Term: 450 mg/m3 - 75 ppm

ACGIH Long Term: 50 ppm

CNS and liver effects (listed under Dipropylene glycol methyl ether)

National DENMARK Long Term: 309 mg/m3 - 50 ppm; Short Term: 618 mg/m3 - 100 ppm

Predicted No Effect Concentration (PNEC) values

dipropyleneglycol methyl Exposure Route: Fresh Water; PNEC Limit: 19 mg/l

ether

CAS: 34590-94-8

Exposure Route: Marine water; PNEC Limit: 1,9 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 70,2 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 7,02 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 4168 mg/l

Exposure Route: Intermittent release; PNEC Limit: 190 mg/l

Exposure Route: Soil; PNEC Limit: 2,74 mg/kg

Derived No Effect Level (DNEL) values

dipropyleneglycol methyl Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

ether Worker Industry: 65 mg/kg; Consumer: 15 mg/kg CAS: 34590-94-8

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 4 of 11

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 310 mg/m3; Consumer: 37,2 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 1,67 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Not needed for normal use. Anyway, operate according good working practices.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid

Color: white

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available
Initial boiling point and boiling range: Not available

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not available Viscosity: Not available

Kinematic viscosity: Not available Solubility in water: dispersible Solubility in oil: partly soluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: 1.02 g/cm3 Vapour density: Not available Particle characteristics: Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 5 of 11

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

dipropyleneglycol methyl a) acute toxicity

ether

LD50 Oral Rat > 5000, mg/kg

LD50 Skin Rabbit = 9500 mg/kg LD50 Skin Rabbit = 9500 mg/kg LD50 Oral Rat = 5,35 q/kg

2,4,7,9-tetramethyldec-5- a) acute toxicity

yne-4,7-diol

LD50 Oral Rat > 500 mg/kg

LC50 Inhalation Rat > 20 mg/l 1h LD50 Skin Rabbit > 1000 mg/kg

1,2-benzisothiazol-3(2H)- a) acute toxicity

one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 670, mg/kg

reaction mass of: 5- a) acute toxicity

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6] (3:1) LC50 Inhalation Rat = 2,36 mg/l 4h

LD50 Skin Rabbit = 660, mg/kg LD50 Oral Rat = 53, mg/kg

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 6 of 11

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological proper	ties of the comp	onents
Component	Ident. Numb.	Ecotox Data
dipropyleneglycol methyl ether	CAS: 34590-94- 8 - EINECS: 252-104-2	a) Aquatic acute toxicity: LC50 Fish Pimephales promelas > 10000 mg/L 96h
		a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1919 mg/L 48h IUCLID
2,4,7,9-tetramethyldec-5-yne-4,7-diol	CAS: 126-86-3 - EINECS: 204- 809-1	a) Aquatic acute toxicity: EC50 Algae 82 mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = 36 mg/L - 4d
		a) Aquatic acute toxicity: LC50 Fish = 42 mg/L - 4d
		a) Aquatic acute toxicity: NOEC Fish = 32 mg/L - 4d
		a) Aquatic acute toxicity: EC50 Daphnia = 91 mg/L - 2d
		a) Aquatic acute toxicity: NOEC Daphnia = 43 mg/L - 2d
		e) Plant toxicity: EC50 Algae = 15 mg/L - 3d
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	- CAS: 2634-33-5 - EINECS: 220- 120-9 - INDEX: 613-088-00-6	a) Aquatic acute toxicity: LC50 Fish = 2,15 mg/L
		b) Aquatic chronic toxicity: NOEC Algae = 0,0403 mg/L 72h
		b) Aquatic chronic toxicity: EC50 Algae = 0,11 mg/L 72h
		b) Aquatic chronic toxicity: FC10 Algae = 0.04 mg/L 72h

b) Aquatic chronic toxicity: EC50 Algae = 0,0403 mg/L 72h
b) Aquatic chronic toxicity: EC10 Algae = 0,04 mg/L 72h
b) Aquatic chronic toxicity: EC50 Daphnia = 3,27 mg/L 48h
NOEC Daphnia = 1,2 mg/L 21d

reaction mass of: 5-chloro-2- CAS: 55965-84- a) Aquatic acute toxicity: EC50 Daphnia = 0,12 mg/L 48 methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- 611-341-5- isothiazol-3-one [EC no. 220-239- INDEX: 613- 613- 167-00-5

a) Aquatic acute toxicity: LC50 Fish = 0,22 mg/L 96
a) Aquatic acute toxicity: EC50 Algae = 0,048 mg/L 72
b) Aquatic chronic toxicity: NOEC Algae = 0,0012 mg/L 72
b) Aquatic chronic toxicity: NOEC Fish = 0,098 mg/L - 28 d

b) Aquatic chronic toxicity: NOEC Daphnia = 0,004 mg/L - 21 d

12.2. Persistence and degradability

Component Persitence/Degradability:

dipropyleneglycol methyl ether Readily biodegradable

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 7 of 11

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Clean waste packaging should be recycled when possible and authorized by the authority.

Hazardous waste: No Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

ADR-Hazard identification number: NA

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 85 g/l

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 8 of 11

```
Regulation (EU) n. 2020/878
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
```

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 28, 40, 55, 72, 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

National regulations

Code

MAL-kode: 1-3 (1993)

Lagerklasse (TRGS-510): 12 - Non-combustible liquids, that cannot be assigned to any of the aforementioned LGK

German Water Hazard Class.

Class 1: slightly hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Description

H317	May cause an allergic skin reaction.			
H318	Causes serious eye damage.			
H412	Harmful to aquatic life with long lasting effects.			
Code	Hazard class and hazard category	Description		
3.3/1	Eye Dam. 1	Serious eye damage, Category 1		
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1		
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3		

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

Print date 10/02/2023 Production Name **ULTRACOAT EASY 10** Page n. 9 of 11 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

 $\hbox{RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.}$

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

 $v P v B \colon Very \ Persistent, \ Very \ Bioaccumulative.$

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 3: Composition/information on ingredients

- SECTION 8: Exposure controls/personal protection

- SECTION 9: Physical and chemical properties

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 10of 11

- SECTION 11: Toxicological information - SECTION 15: Regulatory information

- SECTION 16: Other information

Print date 10/02/2023 Production Name ULTRACOAT EASY 10 Page n. 11of 11