



Image Represents 1.78 M2

| | |
|--------------------|---|
| Species: | European Oak |
| Features & Finish: | Smoke, Oil, Sunken Knots, Cracks |
| Size: | 20 x 189 x 1860mm / 4mm wear layer |

Colour and grain

This product is a fumed product (ammonia treatment). The reaction on the wood which gives the darker colour is dependent on the tannin content of the wood (**the more tannin the darker the result**) The tannin content depends on the origin of the Oak but even trees from the same forest have a different tannin content.

So a fumed product always gives you more colour variation than a stain but the tone is far warmer, highlights character and helps bring nature in to your home. Flooring must be mixed well to achieve a balanced look.

Character

This product contains D & E grade with large repaired sunken and small unrepaired splits to add character to the product. Rustic means the full yield of the log is used so variation in colour, grain, repaired knots, small unfilled worm holes are all to be expected.

Variations within grades

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance.

| Specification | |
|----------------------|---|
| Board Dimensions: | 189 x 20mm x 1860mm (4mm wear layer) |
| Grade: | Rustic + 'B/C/D/E' (Smoke, Oil, Sunken Knots, Cracks) |
| Oak origin: | Mixed EU sources |
| Profile: | T&G |
| Bevel: | G4 1.2mm 'long & short edge' |
| Pack Size: | 2.11 M2 |
| Planks per pack: | 6 Layers, up to 30% starter boards (600mm +) |
| Construction: | Oak Wear Layer, Eucalyptus & Poplar multi ply core |
| Oil (UV Cure): | 2 Coats |
| Adhesive: | E1 |
| Bathroom: | Must never install in this area |
| Conservatory: | Yes |
| Guarantee: | 25 Years Structural - 1 Year Surface Treatment |
| Under floor heating: | Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor) If glued the moisture content of the slab must be <2.5% and the application is full trowel stick with Elka Trowel Adhesive |
| Sheen: | 10% +/- |
| Maintenance: | Elka Oil maintenance kit |
| Installation: | Float over underlay with D3 adhesive, Nail, Screw or stick with Elka flex or Rigid Adhesive |

| PREFINISHED | RUSTIC | A - Grade | B - Grade | C - Grade | D - Grade | E - Grade | For full grading breakdown - visit www.elkaflooring.co.uk |
|-------------|--------|-----------|-----------|-----------|-----------|-----------|--|
| | | - | 10% | 20% | 40% | 30% | |

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

imported and distributed by Unilin Distribution

T: 0844 811 8288

visit our website for full grade specification

www.elkaflooring.co.uk