# **SAFETY DATA SHEET**



Hardener Traffic/Flow

## 1. Identification of the preparation and of the company

Product name and/or code	: Hardener Traffic/Flow
Manufacturer	: Bona AB Box 210 74 SE-200 21 MALMÖ SWEDEN Tel. +46-(0)40-38 55 00
e-mail address of person responsible for this SDS	: marie.holmgren@bona.com
Product use	: Hardener

## 2. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	:	R43
Human health hazards	:	May cause sensitization by skin contact.
Additional warning phrases	:	Contains isocyanates - See information supplied by the manufacturers. This information is supplied in the current Safety Data Sheet.

## 3. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS number	%	EC number	Classification	
Alifatic Polyisocyanate		50 - 75		R43	[1]
See section 16 for the full text of the R-phrases declared above					

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

### 4. First aid measures

#### First aid measures

<ul> <li>In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.</li> </ul>
<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.</li> </ul>
<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.</li> </ul>
: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do not induce vomiting.</li> </ul>

Date of issue/Date of	: 2009-03-17.	Page: 1/6
revision		



## 5. Fire-fighting measures

5. File-lightin	y measures
Extinguishing media	: Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray or mist. Not to be used : water jet.
Recommendations	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.
6. Accidental	release measures
Personal precautions	: Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
Spill	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days

parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

## 7. Handling and storage

Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

#### Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

Date of issue/Date of revision	: 2009-03-17. Page: 2/6
	Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
	Put on appropriate personal protective equipment (see section 8).
	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
	Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
	Keep container tightly closed. Precautions should be taken to minimize exposure to atmospheric humidity or water. CO <sub>2</sub> will be formed, which, in closed containers, could result in pressurization. Care should be taken when re-opening partly-used containers. Keep away from heat, sparks and flame. No sparking tools should be used.
	To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
	In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Handling	: Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

Powered by

## 7. Handling and storage

Comply with the health and safety at work laws.

#### Storage

: Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from heat and direct sunlight.

Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols, water.

No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not empty into drains.

## 8. Exposure controls/personal protection

## Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

#### Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

Engineering measures	:	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. (See Personal Protection.)
Occupational exposure limits	:	Not available.
Personal protective equipme	<u>ent</u>	
Respiratory system	:	By spraying: air-fed respirator. By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask.
Skin and body	:	Personnel should wear antistatic clothing made of natural fibers or of high- temperature-resistant synthetic fibers.
Hands		
Gloves	:	For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

: Use safety eyewear designed to protect against splash of liquids.

#### Environmental exposure controls

**Eyes** 

Do not allow to enter drains or watercourses.

## 9. Physical and chemical properties

Physical state	: Liquid.
Odor	: Sweetish. [Slight]
Color	: Colorless.
Flash point	: Closed cup: 65°C (149°F) [Setaflash.]
Relative density	: 1,09
Solubility	: Insoluble in the following materials: cold water and hot water.

Date of issue/Date of revision	: 2009-03-17.	Page: 3/6
		Powered by

## 10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids, amines, alcohols, water.

Uncontrolled exothermic reactions occur with amines and alcohols.

The product reacts slowly with water, resulting in the production of carbon dioxide. In closed containers, pressure buildup could result in distortion, expansion and, in extreme cases, bursting of the container.

## **11.** Toxicological information

Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin. Repeated or prolonged contact with irritants may cause dermatitis. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains Alifatic Polyisocyanate. May produce an allergic reaction.

Acute toxicity	
<b>Conclusion/Summary</b>	: Not available.
Chronic toxicity	
<b>Conclusion/Summary</b>	: Not available.
Carcinogenicity	
<b>Conclusion/Summary</b>	: Not available.
<u>Mutagenicity</u>	
<b>Conclusion/Summary</b>	: Not available.
Teratogenicity	
<b>Conclusion/Summary</b>	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.

## **12.** Ecological information

There is no data available on the preparation itself. Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

# Aquatic ecotoxicityConclusion/Summary: Not available.Biodegradability: Not available.Conclusion/Summary: Not available.



#### 13. **Disposal considerations**

Do not allow to enter drains or watercourses. Residues in empty containers should be neutralized with a decontaminant (see section 6).

Dispose of according to all federal, state and local applicable regulations.

European waste catalogue (EWC)	: The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

**Hazardous waste** 

: Yes.

#### **Transport information** 14.

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

<u>Sea</u>		
Special provisions	:	Not available.
Marine pollutant	:	No.
Air		

**Special provisions** 

: Not available. The "viscosity exemption" provisions do not apply to air transport.

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

#### **Regulatory information** 15.

:	The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:
:	
	Irritant
4	R43- May cause sensitization by skin contact.
:	<ul> <li>S2- Keep out of the reach of children.</li> <li>S24- Avoid contact with skin.</li> <li>S37- Wear suitable gloves.</li> <li>S46- If swallowed, seek medical advice immediately and show this container or label.</li> <li>S60- This material and its container must be disposed of as hazardous waste.</li> </ul>
÷	Alifatic Polyisocyanate
÷	Europe inventory: Not determined.
:	Contains isocyanates - See information supplied by the manufacturers. This information is supplied in the current Safety Data Sheet.

## 16. Other information

CEPE Classification	: 5
Full text of R-phrases referred to in sections 2 and 3 - Europe	: R43- May cause sensitization by skin contact.
The information in this Safet	y Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.
Date of issue/Date of revision	: 2009-03-17.
Version	: 1
Indicates information that	has changed from previously issued version.
Notice to reader	

Date of issue/Date of	: 2009-03-17.	Page: 5/6
revision		



## 16. Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

